

centrali a larga banda

broad band TV amplifying head-ends


White Line

LTEfree™



Nuova serie di centralini da interno autoalimentati con alimentatore switching integrato. Amplificatore schermato tramite meccanica in pressofusione. Regolazione dei segnali in ingresso mediante attenuatori o potenziometri e possibilità di telealimentazione dai singoli ingressi tramite jumper interni. Sono disponibili in varie configurazioni di ingressi con amplificazione fino a 30 dB e livelli di uscita massimi da 114 a 117 dB μ V. Ideali per la distribuzione dei segnali DTT in piccoli condomini.

New range of indoor auto-supplied head-ends with built-in switching power supply. Amplifier shielded by die-casting mechanics. Adjustment of the input signals by attenuators or potentiometers and remote power supply from single inputs by inside jumpers. Various versions available with amplification up to 30 dB and maximum output level from 114 to 117 dB μ V. Ideal for the DTT signal distribution in small apartment buildings.

codice code LTEfree™	ingressi inputs	bande bands	guadagno (dB) gain		livello uscita (dB μ V) output level		Adj Reg	fig. rumore (dB) noise figure		uscite outputs n°	alimentazione power supply	consumo consumption
			VHF	UHF	VHF	UHF		VHF	UHF			
83519AL	4	BIII, B.IV, B.V, UHF	20	20	108	114	0...15	3	7	1	230V \pm 10% 50Hz	1.5 W
83520AL	3	BIII, UHF, UHF	30	30	108	114	0...15	3	7	1	230V \pm 10% 50Hz	2.2 W
83521AL	4	BIII, B.IV, B.V, UHF	30	30	108	114	0...15	3	7	1	230V \pm 10% 50Hz	2.2 W
83523AL	3	BIII, B.IV, B.V	20	20	108	114	0...15	3	4	1	230V \pm 10% 50Hz	1.5W
83525AL	3	BIII, B.IV, B.V	30	30	108	114	0...15	3	5	1	230V \pm 10% 50Hz	2.2 W
82452L	4	BIII, B.IV, B.V, UHF	30	30	110	117	0...20	3	8	1	230V \pm 10% 50Hz	2.7 W
82454L	3	BIII, B.IV, B.V	30	30	110	117	0...20	3	5	1	230V \pm 10% 50Hz	2.7 W
82455L	4	FM, BIII, UHF, UHF	30	30	110	117	0...20	3	7	1	230V \pm 10% 50Hz	2.7 W
82459L	3	BIII, UHF, UHF	30	30	110	117	0...20	3	8	1	230V \pm 10% 50Hz	2.7 W
82462L	1	BIII + UHF	30	30	110	117	0...20	3	4	1	230V \pm 10% 50Hz	2.7 W
 82462AG	1-2	Log o BIII, UHF	30	30	110	117	0...20 VHF AGC UHF	3	4	1	230V \pm 10% 50Hz	2.7 W

 : LTEfree™ Limita disturbo LTE / Reduces LTE interference